Issued on 2019-01-24

Products Information Data Sheet

These products are hermetically sealed state in a vessel, and are exempted from Safety Data Sheet regulations. However, this manual provides you with referential information to safety use the products.

Section 1 - Products and Company Identification

Products name

Carbon Zinc Batteries(R)

Products sizes

R20 R14 R6 R03

Company

TOSHIBA LIFESTYLE PRODUCTS & SERVICES CORPORATION

Address

25-1, Ekimae-honcho, Kawasaki-ku, Kawasaki,

Kanagawa 210-8543, Japan

Telephone

+81-44-577-0142

Fax

+81-44-222-6264

Section 2 - Composition/Information on Ingredients

Ingredients	CAS#	PRTR	Weight/Content
Manganese dioxide (MnO ₂)	1313-13-9	1-412	17~35wt%
Acetylene black (C)	1333-86-4	Not regulated	3∼7wt%
Zinc chloride (ZnCl ₂)	7646-85-7	1-1	4∼9wt%
Ammonium chloride (NH ₄ CI)	12125-02-9	Not regulated	0.1~1wt%
Zinc(Zn)	7440-66-6	Not regulated	15~40wt%
Lead (Pb)	7439-92-1	1-304	0.05~0.15wt%

Section 3 - Summary of Danger and Toxicity

Fatal danger and toxicity

No information available

Danger and toxicity

Chemical ingredient is hermetically sealed in a vessel, so the

product is neither dangerous nor toxic as a cell.

Zinc chloride which is the contents of cell is an acute toxic. If

adhering to skin, skin may cause inflammation.

Effect to environment

Although no information is available as a cell.

Overview of prospective

A cell may break or be shorted by an external mechanical or

emergency

electrical stress.

Section 4 - First Aid Measures

There is no problem in the normal state. But take the following measures when the contents have begun to leak by the destruction of the battery.

Inhalation

If a person inhaled steam, move to the place where air is fresh immediately. If he/her feels ill, immediately call a doctor for

therapy and treatment.

Skin

If the content adheres to skin, immediately wash it with a large

amount of clean water and soap promptly. If irritating, consult a

Eyes

If the content enters eyes, rinse eyes with a large amount of

clean water for more than 15 minutes, and consult a doctor.

Ingestion

If a cell is swallowed, immediately call a doctor for therapy and

treatment.

Issued on 2019-01-24

Section 5 - Fire Fighting Measures

Fire extinguishers : Powder extinguisher, foam extinguisher, carbon dioxide gas

extinguisher, large amount of dry sand

Specific firefighting method : In the initial state of a fire, move cells/batteries from near the

fire source, to a safe location. At that time, work at a windward location, as far as possible, and be sure to put on a protective

breathing mask.

Protection of firefighting

personnel

Be wear protective breathing masks, gloves, glasses and

helmet for the keeping safe. (Preferably, use a self-feeding

type mask.)

Section 6 - Action upon Leakage and Removing Method

A cell hermetically contains constituents in a vessel, so contents normally may not leak out. However, if the contents leaks because of a mechanical or electrical stress, wipe with liquid-boric to absorb it, and collect in a vessel. After that, flush the site with a large amount of water. At that time, be sure to put on protective-gloves, glasses and mask. (Preferably, use a self-feeding type mask.)

Section 7 - Handling and Storage

Handling : Never solder a cell body.

Do not contact cell terminals between each other, or with another conductor. Neither throws into fire, decompose, heat, dent, deform, charge nor drop a battery. Do not dip a cell in

water or seawater.

Storage : Store cells without direct sunlight, high temperature, high

humidity, rain, dew, etc., and select a storage location with a temperature as low as possible (preferable temperature 10-25°C and relative humidity 70% or less). In addition, keep cells away from dangerous matter such as combustible or ignitable materials. Absolutely never place a cell in contact with a combustible or conductive substance. Prepare appropriate

firefighting equipment.

Note : See handling and storing precautions described in the product

catalog, specification, etc.

Section 8 - Prevention from Exposure

Protection of respiratory

ory

Not required in a normal operating state

organs

Protection of eyes

Not required in a normal operating state

Other protective tools etc.

Not required in a normal operating state

Section 9 - Physical and Chemical Properties

Shape : Cylindrical. Contents are sealed in a stiff stainless steel vessel.

PH
Boiling point/boiling range

Not applicable because a cell is not soluble with water.

Melting point

No information

Nicitally point

No information

Decomposition temperature

No information

Flash point

No information

Page 3/4

Issued on 2019-01-24

Section 10 - Stability and Reactivity

Conditions to be avoided If a number of cells are mixed up without insulating terminals,

they may short and possibly heat, break and ignite. When a cell is charged, possibly in bursting the electrolyte etc. Or, it may possibly burst or fire. If a cell is heated or thrown into fire, it may explode or fire with the electrolyte etc. bursting from inside

of the cell.

If decomposed, there is a possibility of overheating or fire due

to short circuit, and ignition of some material around etc.

Section 11 - Information on Toxicity

There is no toxicity because chemical substances are hermetically sealed in a metal vessel.

As a reference, chemical substances composing a cell are described below.

Manganese dioxide

Acute toxicity L_DL_O:45 mg/kg (Intravenous injection, rabbit)

L_D:422 mg/kg (Hypodermic injection, mouse)

Irritation Irritating eyes, nose, throat and skin.

Chronic toxicity If a person is exposed to powder for a long time or repeatedly.

the lung and the nervous system may be affected, possibly causing bronchitis, pneumonia, nervous disease or mental

disease.

Procreation toxicity

Acetylene black

TCL₀:49mg/m³ (Inhalation, mouse)

Acute toxicity

 $L_{D50}:2,000mg/kg > (Rat)$

Carcinogenic property

Zinc chloride

IARC group 2 (May be carcinogenic)

Acute toxicity

TCL₀:4800mg/m³/30min.

L_{D50}:350mg/kg(oral, rat)

Ammonium chloride

Acute toxicity

L_{D50}:1650mg/kg(oral, rat)

Zinc

Acute toxicity LC₅₀:2500mg/m³(Rat inhalation)

TCLo:124mg/m³/50min.(Human, via respiratory tract)

Lead

Acute toxicity LC₅₀:1000ppm/7hours(Rat inhalation)

Section 12 - Ecological Information

No information as batteries.

Section 13 - Disposal Precautions

Disposal of the substance should be done according to the laws and regulations.

Although used cells can be discarded basically as "nonflammable refuse," some local governments sort and collect them at their own discretion. Therefore, observe instructions of the government you belong to, to dispose of the substance. Keep the following discarding precautions :

· Even a used cell sometimes stores electric energy. Therefore, to prevent the battery from short-circuit, isolate cells from each other by a method such as taping +, - terminals of cells, or using the individual housing case of a cell, used when you bought the battery, and orderly encasing batteries in a box, then submit an application of disposal to the local government of your residence. using the designated form.

Issued on 2019-01-24

- Packing cells so that they are not shorted, and prevent the package from being wetted.
- If cells must be discarded in a country other than Japan, observe the instructions of the country and local government.

Section 14 - Transportation Precautions

TOSHIBA Carbon Zinc Batteries are considered to be "dry cell" batteries and are not regulated for purposes of transportation by the U.S. Department of Transportation (DOT), International Civil Aviation Administration (ICAO), International Air Transport Association (IATA) and International Maritime Dangerous Goods Regulations (IMDG). Shipping these batteries is subject to the only requirements by DOT is Special Provision 130 i.e. "Batteries, dry are not subject to the requirements of this subchapter only when they are offered for transportation in a manner that prevents the dangerous evolution of heat (for example, by the effective insulation of exposed terminals)". Shipping these batteries is subject to the only requirements by ICAO and IATA is Special Provision A123 i.e. "An electrical battery or battery powered device having the potential of dangerous evolutions of heat that is not prepared so as to prevent a short-circuit (e.g. in the case of batteries, by the effective insulation of exposed terminals; or in the case of equipment, by disconnection of the battery and protection of exposed terminals) is forbidden from transportation." The International Maritime Dangerous Goods Code (IMDG) regulate them for ocean transportation under Special Provision 304 which says: "Batteries, dry, containing corrosive electrolyte which will not flow out of the battery case is cracked are not subject to the provisions of this Code provided the batteries are securely packed and protected against short-circuits. Examples of such batteries are: alkali-manganese, zinc carbon, nickel metal hydride and nickel-cadmium batteries.

Section 15 - Applicable Laws and Regulations

The laws and ordinances about the battery obey the latest laws and ordinances.

Section 16 - Other Information

The Carbon Zinc cells/batteries fall in the category of "Article" defined by EPA (U.S. Environment Protection Agency), and chemical substances used in a battery satisfy the application exemption conditions (40.crf.720.3.c) as part of "Article," so the batteries are not regulated by TSCA.

Revised Day

January 01, 2019

Preparation This Sheet

TOSHIBA LIFESTYLE PRODUCTS & SERVICES CORPORATION

Engineering Group

Planning & Procurement Dept.

Battery Business Div.